



JET-LUBE **NEW** Gear Guard™ Open Gear Lubricant

A paste-like, viscous lubricant for reducing friction and wear. A heavy-duty compound, specially prepared to penetrate pores of metal, with exceptional “stay-put” characteristics. Provides maximum lubrication and shock-load protection; reduces gear noise; lubricates; and prevents scoring, spalling, or welding of the gear teeth. Gears are assured a smooth, long-lasting, economical and effective coating. It's black color allows for easy coverage and touch up. Resists heat and pressure, will not wash or wear off because of weather, and will not break down after repeated working. Ideal chains - drives. Ideal gears - roller.

Container Type	Size (Oz.)	Item No.	Pkg. Qty.
Aerosol	12	1637218	3

- No dropping point
- Friction-reducing wear additive
- Shock-load protection
- Will not sling off the surface
- Contains Moly
- Rust-preventing additives
- Resists moisture, heat, and pressure
- Temperature range: -25°F to +350°F (-32°C to +175°C)
- 16 oz. can size; 12 oz. net wt.



JET-LUBE **NEW** Food Grade Silicone Food Grade Lubricant

An excellent lubricant for use on processing equipment in all types of food and food-related industries where incidental food contact may occur. Stops sticking, squeaking, and binding of moving parts. An excellent release agent, will not gum, melt, freeze, become rancid, or form unwanted residues. Leaves a clear film that is moisture resistant, long-wearing, odorless, colorless, non-toxic, and non-staining.

Container Type	Size (Oz.)	Item No.	Pkg. Qty.
Aerosol	12	1637219	3

- Non-toxic
- Safe on plastics
- Non-staining
- Colorless and Odorless
- Contains No: 1:1:1 Trichloroethane, Freon TF or SARA listed ingredients
- Temperature range: 0°F to +350°F (-17°C to +177°C)
- 16 oz. can size; 12 oz. net wt.



JET-LUBE **NEW** Oven Chain Lubricant™ Chain Lubricant

The answer to oven chain lubrication. Can also be utilized effectively in gear lubrication applications. Derived from a carefully evolved blend of high-viscosity, non-smoking 550°F (288°C), low odor synthetic fluids and surface tension modifiers. These lower the surface tension of the high-viscosity fluids, allowing them to move effectively to penetrate into the links and pins of the chain and lubricate the chain roller.

Container Type	Size (Lb.)	Item No.	Pkg. Qty.
Pail	35	1637220	1

- Contains PTFE
- Low odor
- Reduced smoke
- Non-corrosive





LUBRICANTS

JET-LUBE



FMG™

Food Machinery Grease (White) NSF H1

A white, aluminum complex grease lubricant of the USDA Authorized H-1 type. Meets and exceeds the requirements of FDA Regulations. Specifically designed for use in the food processing industry where it may have incidental food contact. Formulated to perform in a wide variety of operating conditions. Extremely water-resistant and will remain in place even after frequent washdowns. Its polymer additives provide adhesive/cohesive strength to protect against pound-offs when encountering shock loads.

Container Type	Size (Oz.)	Quantity Per Pkg.	Item No.	Pkg. Qty.
Cartridge	14	1	1637314	1
	14	30	1637221	1

- Extremely water-resistant
- Adhesive and cohesive strength
- Anti-wear and polymer additives
- Resists pound out
- Aluminum Complex
- White
- Meets NSF requirements
- Meets CFR Title 21, Section 178.3570 of FDA Regulations



JET-LUBE



769 Lubricant®

Lubricant and Penetrant

A multipurpose, penetrating, lubricating, moisture displacing, and corrosion-preventative product. For use where salt water, salt spray, or other harsh environments are present. Gives total performance while being environmentally safe, easy to use, and non-flammable. Contains ashless extreme pressure additives and highly refined lubricating oils that provide superior lubricating protection and anti-wear properties. NSF H2.

Container Type	Size	Item No.	Pkg. Qty.
Aerosol	12 Oz. Net Wt.	1637222	3
Spray Bottle	16 Fl. Oz.	1637223	3

- Non-flammable
- Non-evaporating
- Contains no fluorocarbons
- Contains no silicones
- MIL-PRF-81309H (Aerosol) Type II & III, Class II, CO2 Grade
- MIL-C-16173E Grade 3
- MIL-C-23411A VV-P-216B CID A-A-50493C Class B Type I
- Aerosol: 16 oz. can size; 20 oz. net wt.



1637222



1637223

JET-LUBE



EMS™

Water-Based Silicone Lubricant

An emulsified, multi-purpose lubricant that lubricates, waterproofs and protects while being odorless, tasteless and non-staining. Stops sticking, squeaking and binding of moving parts. An excellent release agent and ideal clear, clean lubricant.

Container Type	Size (Fl. Oz.)	Item No.	Pkg. Qty.
Spray Bottle	16	1637224	3

- Non-toxic
- No VOC's
- Non-staining
- Odorless
- Non-flammable
- Low foaming
- Environmentally safe





JET-LUBE



Alco-EP 73 Plus™ Extreme Pressure Multipurpose Grease

A premium, state-of-the-art, multipurpose aluminum complex grease. Contains a highly synergistic blend of rust and oxidation inhibitors, plus extreme pressure and anti-wear additives for maximum performance characteristics. Non-plating, organic EP/anti-wear additives allow this formula to be used where tolerances are low and/or speeds are high. Contains polymer additives; further enhancing the inherent water resistance of an aluminum-complex-based grease. Extremely resistant to rust and corrosion and ideally suited for use in high-moisture areas, including subsea applications.

- High-strength fluid film
- Extreme resistance to rust and corrosion
- Strong adhesion properties
- Pumpable
- Aluminum complex grease
- Timken load: 45 lbs.



Container Type	Size (Oz.)	Quantity Per Pkg.	Item No.	Pkg. Qty.
Cartridge	14	1	1637315	1
	14	30	1637225	1

JET-LUBE



#202 Moly-Lith™ Multipurpose Grease with MoS2

A black, thermally stable, lithium 12-hydroxystearate soap grease containing microfine molybdenum disulfide (MoS2), antioxidants and rust inhibitors. Exceptional resistance to the effects of heat, water, weathering, oxidation and heavy loads. Provides unexcelled protection wherever dirt, dust, high humidity, rain and adverse temperatures are a problem. Highly adhesive, pumpable and stable.

- Contains Moly for friction reduction and high load capacity
- Superior metal adhesion
- Pumpable
- Resistant to water, heat, weathering and oxidation
- Excellent work stability
- Lithium 12-hydroxystearate grease
- Contains Molybdenum disulfide (MoS2)



1637316
1637226



1637227

Container Type	Size	Quantity Per Pkg.	Item No.	Pkg. Qty.
Cartridge	14 Oz.	1	1637316	1
	14 Oz.	30	1637226	1
Pail	35 Lbs.	1	1637227	1