






ALL-PURPOSE SILICONE LUBRICANT



LUTM206

- 
™ Light Pressure Lubricant
- 
™ Minimum - Maximum operational temperature range: Low -50°F (-46°C) High 550°F (288°C)
- 
™ 5% Silicone
- 
™ Features Spray Anyway™ nozzle
- 
™ HMIS Hazard Rating: Health (2) • Flammability (4) • Reactivity (0)

- Works from -50°F to 550°F
- Does not interfere with painting operations
- Compatible with most surfaces



Sprayon® LUTM206 All-Purpose Silicone Lubricant is an economical lubricant for applications where petroleum based products are not desired. This 5% silicone formula protects against air and moisture to retard oxidation and corrosion. It virtually eliminates friction and sticking to improve high-speed production. Leaves a long-lasting film that is compatible with most surfaces. Equipped with an extension tube for hard-to-reach areas.

LUBRICANTS

USES

- Windows
- Rubber components
- Doors
- Plastic assemblies
- Drawers
- Dissimilar metals
- Hinges
- Sliding wood surfaces
- Springs
- Layout tables
- Leather
- Weatherstripping



LU206

APPLICATION

Maximum performance is achieved when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale. Product should be sprayed in a well ventilated area. Sprays best at room temperature (70F.) Shake well before using. Spray at a distance of 10" to 14" from surface.

PERFORMANCE

PLASTIC SAFE: Yes
TEMPERATURE RANGE:
LOW: -50°F
HIGH: 550°F
LOAD CAPACITY: Light

- Penetrant
- Water-Displacer
- Rust Inhibitor
- Eliminates sticking
- Improves high speed production
- Retards oxidation and corrosion

PHYSICAL

APPEARANCE: Clear liquid
ODOR: Slight solvent
PROPELLANT: Hydrocarbon
WT./GAL.: 5.43
SPECIFIC GRAVITY: 0.65
VISCOSITY: Medium
PAINTABLE: Yes
% VOC AEROSOL: 94.00%
V.O.C. COMPLIANT CALIFORNIA: Yes
V.O.C. COMPLIANT OTC STATES: Yes
FLAMMABLE: Yes
FLASH POINT: <0°F
HAZARD RATING: 2,4,0
SHELF LIFE: 3 years from date of manufacture

PACKAGING

Stock #: S00206
UPC Code: 0-75577-90206-4
Fill Wt.: 10 oz.
Per Case: 12
Carton Dimensions:
L 10-7/8" x W 8-3/16" x H 8"

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS:
sprayon.com
CUSTOMER SERVICE:
1-800-777-2966
TECHNICAL INFORMATION:
1-800-251-2486

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.



© 2010 Sprayon® Products Made in U.S.A.

Distributed by:

Lawson Products, Inc.

To order these and other products, contact us:

866-529-7664 lawsonproducts.com

PRESERVE. PROTECT. PREVENT.



Sprayon® Products
101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
1-800-777-2966

310-PDS-LU206